

TWS-N | HYDRAULIC TORQUE WRENCHES - SQUARE DRIVE





Torque capacities up to 26860 lbf.ft

Torque accuracy of +/- 3%

Working pressure 10000 psi

- ▶ Compact, lightweight aluminum body construction
- ▶ Output torque capacities from 1254 to 26860 lbf.ft (1727 to 36992 Nm)
- ▶ Choice of square drive sizes from ¾" to 2 ½"
- ▶ Reversible square drive for tightening or loosening applications
- ▶ Multi-position reaction arm with safety lock feature
- ▶ Fitted with 360° uni-swivel quick release couplings for easy positioning of hydraulic hoses during operation
- ▶ High quality torque wrench sockets for use with TWS-N range hydraulic wrenches are listed on pages 83 and 84
- ▶ Optional allen hex drives available from ½" to 2 ¼" and 14 to 60 mm (see page 85)



Model number	Torque capacity		Square drive size	Weight including reaction foot (lbs)	Dimensions (in)						
	lbf.ft at 10000 psi	Nm at 700 bar			A	B	C	D	E	F	R
TWS17N	1254	1727	¾"	4.2	5.08	6.58	3.55	5.16	2.01	2.88	0.99
TWS45N	3289	4529	1"	10.6	6.58	8.59	4.77	6.7	2.68	3.86	1.34
TWS100N	7427	10064	1 ½"	19.8	8.79	11.54	6.42	8.31	3.62	5.32	1.81
TWS150N	10873	14974	1 ½"	33.1	9.73	12.73	7.56	9.3	3.94	5.56	2.13
TWS370N	26860	36992	2 ½"	71.6	12.96	17.02	9.46	11.35	5.4	8.04	2.6